

CL2P###DxDIN-B

Current Loop/Signal Line protection device with Discrete All-Mode Protection



PO Box 15732
Brooksville, FL 34604
Phone: 888-987-8877
Fax: 1-888-987-8877
www.surgesuppression.com

The Series CL2P devices are designed to protect current loop process instrument, data transmission, control, and signal line circuits. These devices are intended for installation as close to the electrical power source of the equipment as possible so as to allow for a common point for grounding.

This device is for circuits with up to 2 pair of signal lines connected via the detachable terminal strip provided. A ground lug is provided on the top of the unit to insure a low impedance ground discharge path.

The unique design of these devices makes them among the most versatile SPD devices on the market with superior performance specs and a warranty that is second to none.

GENERAL

Description:	Series wired transient voltage surge suppressor with encapsulated Optimal Response Network™ circuitry for protection of current loop and data/signal type circuits.
Application:	Designed for use on data, signal, current loop and control circuits to protect equipment from damaging transients generated between terminals and equipment in the data collection/transmission system.
Warranty:	25 Years Unlimited Free Replacement
Unit Listing:	Listed to UL497B

MECHANICAL

Enclosure:	Plastic, UL 94-5VA
Mounting:	DIN rail mounting foot
Connection Method:	Wire clamping detachable box terminal. Wire size: Lines # 12-22 AWG, Ground # 6-12 AWG.
Shipping Weight:	< 1 lbs

CIRCUITRY

Circuit Design:	Series wired design incorporating discrete all mode protection and utilizing our encapsulated Optimal Response Network™ design to provide lowest possible let-through voltages. All suppression circuits are encapsulated in our high dielectric compound to promote long component life and protection from the environment and/or vibration.
Protection Modes:	Dedicated protection components and circuitry for each mode. Discrete each L-L (Normal Mode) and each L-G (Common Mode)

PERFORMANCE

Maximum Continuous Operating Voltage:	See Table on back
Maximum Continuous Operating Current:	5 A
Series resistance:	0 Ohms per wire
Maximum Data Rate:	100 Kbps
Peak Surge Current per Pair:	L-L 10 kA, L-G 10 kA

Let-Through Voltages Using ANSI/IEEE C62.45 & C62.41 Test Environment: Static, positive polarity. All voltages are peak ($\pm 10\%$).			
Model	Test Mode	Maximum Continuous Operating Voltage (MCOV)	B3/C1 Impulse Wave 6 kV, 3 kA (100 Kbps)
CL2P5DxDIN-B	L-G	14 V	149
	L-L	28 V	149
CL2P12DxDIN-B	L-G	31 V	163
	L-L	62 V	163
CL2P24DxDIN-B	L-G	38 V	220
	L-L	76 V	220
CL2P48DxDIN-B	L-G	102 V	295
	L-L	204 V	295
CL2P130DxDIN-B	L-G	175 V	470
	L-L	350 V	470

Note: x = 2, 4

